

# WARNING

# CBC.P

For EVA glue - Use any granulated glue within the Temperature range of 210° Celsius / 410° Fahrenheit to 180° Celsius / 356° Fahrenheit.

For PUR glue - Use any granulated glue within the Temperature range of 110° Celsius / 230° Fahrenheit to 150° Celsius / 302° Fahrenheit

This machine will only work correctly if the proper glue is used. This machine come with EVA glue in the pot for temperature range of 210° Celsius / 410° Fahrenheit to 180° Celsius / 356° Fahrenheit.

**DO NOT MIXED DIFFERENT TEMPURATURE GLUES**  
**We recommend the following glues:**



**EVA - Jowat (ref. 288.60)**  
**Process Temp 180 - 200° C**

**PUR - Jowat (ref 608.00/608.01)**  
**Process Temp 110 - 130° C**



**• EVA - Kleiberit (ref. 773.3)**  
**Process Temp 180 - 200° C**

You can use glue from other brands as long as it has an application temperature range mention above. Please follow the glue manufacturer recommended glue temperature for best applications.

In case you are using PUR in the glue pot, we recommend draining and cleaning the glue pot every day, following the glue manufacturer strict recommendations.

**Damage as a result of incorrect glue or misuse of the glue system may result in the warranty being voided.**

For more information or assistance please visit our website at: [www.maksiwa.com](http://www.maksiwa.com) and our **YouTube page: Maksywa USA** where you can find step by step instructions on how to set up your equipment, instruction manuals among other useful tips.

For any further assistance, contact us at: **+1 (844) 319-6594** or email us at [customer.service@maksiwa.com](mailto:customer.service@maksiwa.com)



**Maksiwa International Inc. | 990 S Rogers Cir Suite 11, Boca Raton, Florida | 33487**

+1 (844) 319-6594  
+1 (754) 205-6717

[customer.service@maksiwa.com](mailto:customer.service@maksiwa.com)

[maksiwa.com](http://maksiwa.com)



/maksywausa